



C3-RS1000 O.L.E.D.

2-Way O.L.E.D. Remote Start w/ 6 Channel Alarm

RS-1000 OLED *NEW 900MHz*, Six-Channel Alarm System with Remote Car Starter and Two Way FM/FM Paging O.L.E.D. Remote Transmitter

STANDARD COMPONENTS:

- **6 Channel Alarm** and Remote Car Starter with **5 on-board MICRO relays** for parking lights, starter, accessories, ignition 1&2 and one additional relay / socket for starter disable.
 - **C3 Compatible with On-board Serial Port for AP Data Link Data Bus Integration**
 - Two-way paging receiver and transmitting remote with 3-color LCD screen using FM frequency bands for transmitting and receiving at **900 megahertz**. **Unit will transmit and receive up to 1 MILE**. Unit also includes 24-hour clock with meter minder and temperature indicator and countdown run timer.
 - **New MANCHESTER CODE encoder**.
 - **NEW STYLE Two-way, window mount SUPER EXTENDED RANGE** transceiver antenna module.
 - **One 5-button extended range FM, standard 900-megahertz SLIDE COVER** remote transmitter.
 - SIS-11 Super Intelligent Sensor with dual stage shock / glass sensitivity.
 - Discrete Temperature Sensor that communicates in-car temperature with LCD remote.
 - Window-mount Knock Sensor for driver paging.
- Plug-in super bright mini-BLUE LED** and push-type valet/override switch.

TWO-WAY O.L.E.D. REMOTE OPERATION:

- 5-button configuration with selectable Button Lock to prevent accidental mis-use.
 - Uses a rechargeable battery via Mini USB type connector w/ wall charger included.
 - Battery life indicator and power save mode
 - Full color (**O.L.E.D. Organic Light Emitting Diode**) with over 100 icons and animation screens.
 - Optional Two Car Operation with LCD transmitter only
 - Transmits on FM band and receives on FM band.
 - 24-hour digital clock with count down timer for parking meter reminder. The clock doubles as a temperature indicator for monitoring in-car temperature. Displays in Fahrenheit or Celsius.
 - Multiple audible confirmation tones as well as vibrator mode for paging.
- 2-way Transmitter Range Check Indicator

ALARM FEATURES:

- Six Channels of outputs (3 dedicated to lock/unlock, trunk and remote start / 3 auxiliary outputs)
- Dedicated function buttons on LCD remote and 4-button standard remote transmitter.
- Code learning / Anti-scan receiver with programmable code hopping.
- Back-up memory system
- Selectable Chirp Confirmation (OEM Style lock only chirp confirmation)
- Comfort Feature with OEM systems having key / remote control power window roll-up
- Dedicated remote panic and car locator
- Passive arming by-pass from the remote
- Parking light flash with dual polarity relay on-board
- Plug-in dual stage SIS-11 shock sensor with sensor by-pass from the remote
- Starter disable output with relay and socket included
- Dome light illuminated entry output
- Dual polarity (+/-) door lock outputs with optional driver's door priority two step unlock
- Additional positive and negative inputs
- 500 mA grounded outputs for starter disable and door lock/unlock
- Programmable momentary, latched or timer on 3 auxiliary channels.
- Programmable manual / passive arming with true last door arming with auto re-arm on
- Programmable Single / Double Pulse Unlock (**7 new timing adjustments**)
- Programmable Parking lights (flash or constant)
- Programmable Pathway Illumination (on / off)
- Programmable voltage sense for delayed dome lights (on / off)
- Programmable horn and siren chirp delete
- Programmable ignition control lock and unlock
- Programmable pulse time for lock and unlock (.9 sec. / 3 sec.)

REMOTE CAR STARTER FEATURES:

- 5 On-Board Relays:
 1. Ignition 1
 2. Ignition 2
 3. Starter
 4. Accessory
 5. Parking Light
- 3rd Ignition (-) output
- **Dedicated Second Start wire**

- **Dedicated Ground out when running**
 - **GM- Non starter wire timing compatible**
 - Ground when start (-) output
 - New Turbo Timer feature
 - 2nd Accessory (-) output
 - Selectable one or two push Safety Start
 - Programmable gasoline or diesel with 10, 15, or 20 second Wait-to-Start
 - Hood pin switch safety input (pin switch included)
 - Selectable RPM / Voltage Start
 - RPM / Voltage / Hi-Low level check
 - Timer control start option
 - Sensor control output during start
 - Temporary Stop Feature
 - Factory Alarm Disarm and Rearm signal output
 - Programmable factory keyless door locking before and after start
 - Programmable start status output with shock sensor bypass
 - 45 second door / dome light bypass after ignition is turned off.
 - Programmable Ignition 2 (on / off)
 - Programmable 3 hour timer start
 - Programmable 1 / 3 hour timer start
 - Selectable Run Timer (5/10/20/30 minutes)
 - Selectable Gasoline / diesel
- Selectable Diesel warm-up time